

1/PRTS

09/600847

532 RPT/PCT/PTC 24 JUL 2000

BEARING MAT FOR SUPPORTING AN EXHAUST GAS CATALYST

09/600847

The invention relates to a bearing mat for supporting in a metallic catalyst housing an exhaust gas catalyst for cleaning motor vehicle exhaust gases. The bearing mat is arranged on the periphery of the ceramic carrier body of an exhaust gas catalyst and seals the annular gap between the ceramic carrier body and the catalyst housing consisting of a metallic material. Said bearing mat is intended to permit a safe and vibration-free support of the ceramic carrier body and has to compensate any change occurring in the width of the annular gap to be sealed when the metallic catalyst housing expands at the operating temperature preset by the combustion exhaust gases. Furthermore, the bearing mat forms a heat-insulating layer on the inner wall of the catalyst housing and reduces the outwardly transmitted sonic noise generated by the flowing exhaust gases.

Within the framework of the measures known, the bearing mat consists of short inorganic fibers, an organic binding agent, as well as embedded particles consisting of expanding material, for example mica or vermiculite, which expands under the influence of heat and causes the volume of the bearing mat to increase at the operating temperature. The inorganic fibers embedded in the binding agent consist of ceramic staple fibers or crushed SiO_2 filaments with an average length of a few

millimeters (DE-U 93 11 571). A bearing mat with short inorganic fibers exhibits a tendency to erosion and abrasion. The fibers as well as the particulate expanding material are discharged together with the flowing combustion exhaust gases, with the consequence that sealing of the annular gap deteriorates and erosion increases. When a fiber material made of longer filaments is used, there is the risk of fibers being blown out, though only to a lesser extent. However, the formation of bridges and cross-linkage of the filaments obstruct expansion of the mat and the effect of the expanding material is prevented from becoming fully effective. Finally, there is the problem that the expanding property of vermiculite and mica starts to take effect only at high temperatures. The known supporting mats are not suitable or suitable only to a limited extent for exhaust gas catalysts employed for cleaning the combustion exhaust gases of diesel engines because the exhaust temperatures occurring with diesel fuel are inadequate for initiating an expanding effect of the bearing mat.

The invention is based on the problem of proposing a bearing mat for exhaust gas catalysts that is safely prevented from being blown out and which effectively seals the annular gap between the exhaust gas catalyst and the catalyst housing both at low and high exhaust gas temperatures.

The problem is solved according to the invention by a bearing mat in the form of a binding agent-free, multi-layered flat structure consisting of heat-stable threads, said flat structure being mechanically reinforced by quilting seams, whereby

- the threads consist of a crimped yarn of filaments and are fixed by the quilting seams in the flat structure under tensile stress; and
- the quilting seams are produced with a sewing thread with a thermal stability that is lower than the operating temperature of the bearing mat.

Methods for reshaping unstructured filament yarns into crimped, textured yarns with a textile appearance are known. The resulting crimped yarns are voluminous and characterized by high elasticity. According to the invention, the threads consisting of a crimped yarn are laid under tensile stress to form a flat structure that has the usual thickness of bearing mats. The threads are fixed within the flat structure by quilting seams, whereby the tensile stress is maintained. The sewing thread used for the quilting seams consists of a material whose thermal stability is lower than the operating temperature of the bearing mat. When the bearing mat installed in the housing of the catalyst is heated for the first time to the operating temperature preset by the combustion exhaust

gases, the quilting seams are destroyed, whereby deformation energy stored in the crimped yarn is being released as the tensile stress of the thermally stable threads is being relieved. The liberated deformation energy is substantial and permits a considerable increase in the volume of the flat structure. The sealing power of the bearing mat installed between the catalyst housing and the exhaust gas catalyst is accordingly high as soon as the quilting seams have been destroyed when the bearing mat is heated to the operating temperature for the first time. The increase in volume of the bearing mat as defined by the invention, which starts with the dissolution of the quilting seams, is not dependent upon the temperature.

Therefore, the bearing mat as defined by the invention can be employed in connection with both exhaust gas catalysts that are operated with relatively low temperature, and with exhaust gas catalysts for hot combustion exhaust gases, as usually found with Otto engines. Owing to the fact that the bearing mat as defined by the invention contains neither expanding material in the form of particles, nor fractured pieces of fiber material, but exclusively consists of long filament threads, the risk of any erosion or abrasion caused by the flowing combustion exhaust gases is low.

The crimping yarn preferably consists of SiO_2 filaments and/or filaments made of textile glass and/or Al_2O_3 -containing inorganic filaments. However, other crimped yarns having high thermal stability and consisting of organic or inorganic materials are not to be excluded. According to a further development of the invention, the latter teaches that seams consisting of a thermally stable thread are provided on the cutting edges of the bearing mat. The seams on the cutting edges produced with a thermally stable thread material assure additional edge protection and contribute to a further improvement in preventing the blowing out in the bearing mat of the invention. Suitable are threads that still have adequate tensile strength at the operating temperature of the bearing mat. Considered can be threads made of textile glass, SiO_2 , metals and the like.

Furthermore, the object of the invention is a process for producing the bearing mat with the following features:

- (a) Crimped yarn consisting of thermally stable filaments is taken off from rolls in a plurality of strands and laid under tensile stress on a transporting device moving transversely to the direction of pull-off to form a plane, multi-layered flat structure.

(b) The flat structure, which is moved on with the transporting device, is mechanically reinforced with quilting seams in such a way that the threads of the flat structure continue to be under tensile stress when the flat structure is removed from the transporting device.

(c) A sewing thread is employed for the quilting seams that has a thermal stability which is lower than the operating temperature of the bearing mat.

As a further development of the invention, the latter provides the instruction that mats are punched from the continuous web, the latter having been mechanically reinforced with quilting seams, and that prior to or after the punching process, seams are applied within the zone of the cutting edges, using a thread consisting of a thermally stable material.

The invention is explained in the following with the help of the drawing showing only one exemplified embodiment. The single drawing shows a flow diagram of the process for producing bearing mats for exhaust gas catalysts.

In a first process step of the manufacturing process shown in the figure, crimped yarn consisting of inorganic filaments

is pulled off from the rolls 2 in a plurality of strands 1 and deposited under tensile stress on a transporting device 3 moving transversely to the direction of take-off, in order to form a plane, multi-layered flat structure 4. As the strands 1 are being laid, they are hooked into the edge-side chains 5 of the transporting device 3. The tensile stress in the strands 1 is maintained in this way. The thickness of the flat structure depends on the type of use. Bearing mats with a thickness of just a few millimeters up to a few centimeters are used depending on the diameter and weight of the catalyst for which the bearing mat is intended. The thickness of the flat structure is adjusted accordingly.

The transporting device 3 passes through a station 6, in which the flat structure 4 is mechanically reinforced with quilting seams 7 in such a way that the threads of the flat structure continue to be under tensile stress when the flat structure 4 is removed from the transporting device 3. A sewing thread is employed for the quilting seams 7 that has a thermal stability which is lower than the operating temperature of the bearing mat.

In a last process step, mats 8 are punched out from the continuous web that has been mechanically reinforced with quilting seams 7, whereby prior to or after the punching process, seams 9 are applied within the zone of the cutting

edges, using a thread consisting of a thermally stable material.

It is understood that the material web mechanically reinforced with quilting seams can also first be wound to an endless ribbon, and that the individual mats can then be produced by punching processes at the location of the customer.

The process shown in the figure is employed for producing binding agent-free bearing mats for supporting exhaust gas catalysts. Said bearing mats consist of a multi-layered flat structure made of inorganic threads, which is mechanically reinforced by quilting seams. It is important for the predetermined function of the bearing mat that the threads consist of a crimped yarn consisting of filaments; that said threads are fixed in the flat structure under tensile stress by the quilting seams; and that the quilting seams are produced with a sewing thread having a thermal stability lower than the operating temperature of the bearing mat. The crimped yarn preferably consists of SiO_2 filaments and/or filaments made of textile glass and/or Al_2O_3 -containing filaments. Synthetic sewing threads which are not heat-stable and which are destroyed when the bearing mat is heated to the operating temperature are used for the quilting seams. The destruction of the sewing threads liberates deformation energy of the crimped yarn, whereby the volume of the bearing mat expands and

1911	1912	1913	1914	1915	1916	1917	1918	1919	1920	1921	1922	1923	1924	1925	1926	1927	1928	1929	1930	1931	1932	1933	1934	1935	1936	1937	1938	1939	1940	1941	1942	1943	1944	1945	1946	1947	1948	1949	1950	1951	1952	1953	1954	1955	1956	1957	1958	1959	1960	1961	1962	1963	1964	1965	1966	1967	1968	1969	1970	1971	1972	1973	1974	1975	1976	1977	1978	1979	1980	1981	1982	1983	1984	1985	1986	1987	1988	1989	1990	1991	1992	1993	1994	1995	1996	1997	1998	1999	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2027	2028	2029	2030	2031	2032	2033	2034	2035	2036	2037	2038	2039	2040	2041	2042	2043	2044	2045	2046	2047	2048	2049	2050	2051	2052	2053	2054	2055	2056	2057	2058	2059	2060	2061	2062	2063	2064	2065	2066	2067	2068	2069	2070	2071	2072	2073	2074	2075	2076	2077	2078	2079	2080	2081	2082	2083	2084	2085	2086	2087	2088	2089	2090	2091	2092	2093	2094	2095	2096	2097	2098	2099	2100	2101	2102	2103	2104	2105	2106	2107	2108	2109	2110	2111	2112	2113	2114	2115	2116	2117	2118	2119	2120	2121	2122	2123	2124	2125	2126	2127	2128	2129	2130	2131	2132	2133	2134	2135	2136	2137	2138	2139	2140	2141	2142	2143	2144	2145	2146	2147	2148	2149	2150	2151	2152	2153	2154	2155	2156	2157	2158	2159	2160	2161	2162	2163	2164	2165	2166	2167	2168	2169	2170	2171	2172	2173	2174	2175	2176	2177	2178	2179	2180	2181	2182	2183	2184	2185	2186	2187	2188	2189	2190	2191	2192	2193	2194	2195	2196	2197	2198	2199	2200	2201	2202	2203	2204	2205	2206	2207	2208	2209	2210	2211	2212	2213	2214	2215	2216	2217	2218	2219	2220	2221	2222	2223	2224	2225	2226	2227	2228	2229	2230	2231	2232	2233	2234	2235	2236	2237	2238	2239	2240	2241	2242	2243	2244	2245	2246	2247	2248	2249	2250	2251	2252	2253	2254	2255	2256	2257	2258	2259	2260	2261	2262	2263	2264	2265	2266	2267	2268	2269	2270	2271	2272	2273	2274	2275	2276	2277	2278	2279	2280	2281	2282	2283	2284	2285	2286	2287	2288	2289	2290	2291	2292	2293	2294	2295	2296	2297	2298	2299	2300	2301	2302	2303	2304	2305	2306	2307	2308	2309	2310	2311	2312	2313	2314	2315	2316	2317	2318	2319</
------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	--------